



**PROGYPS PR**  
**869**  
*Satin Plaster Primer*

**PRODUCT DESCRIPTION:**

It is a water-based, acrylic emulsion-based 1/7 concentrated high performance paint primer produced for interior satin plaster surfaces.

**FEATURES:**

- It reduces the consumption of topcoat paint on absorbent surfaces such as satin plaster.
- It penetrates the surface well.
- It prepares a healthy ground.
- Its adherence is high.
- Easy to apply.
- It is environmentally friendly.
- It is economical because it is diluted with 1/7 water.

**PRODUCT INFORMATION:**

Chemical Base Acrylic Based / Water Based  
Appearance / Color Liquid / White  
Dry Film Color Transparent  
Ph 7-10

**PERFORMANCE:**

(23°C, 50% RH)

Density:  $1.1 \pm 0.2$  gr/cm<sup>3</sup>

These values have been obtained as a result of laboratory experiments and are valid for the performance of the finished applications at the end of the full drying period. Since the temperature and humidity values in the construction site environment and the application surfaces and areas will vary, the values may change.

**USAGE AREAS:**

It is used on satin plaster, plasterboard surfaces, old painted/plastered interior surfaces with high absorbency.

**APPLICATION INSTRUCTIONS:**

Surface; It should be cured, dry and solid. It must be cleaned of residues such as oil, grease, dirt, paint, salt vomit that will prevent adhesion. The surface must be rough. If there are significant defects on the application surface, correction should be made with PROPLASTER.

The product is prepared by diluting it with 1/7 water and mixing it with a low speed mixer.



# PROGYPS PR 869

*Satin Plaster Primer*

## **Application Equipment:**

Hand Mixer

Roll

The Product Is Thinned With Water And Applied With A Roller Or Brush To The Surface Preparation Area.

## **LIMITATIONS:**

In order to obtain optimum quality, please obey to the application instructions. Application should not be made in very high temperature, direct exposure to sunlight, very windy, rainy weather. It should not be applied on surfaces where there is a danger of frost. The application should be done between +5 C and +30 C. It should never be applied at temperatures below 5 C. Until the product cures (28 days), it should be protected from rain, water, frost and adverse external factors.

## **CONSUMPTION:**

150-300 gr /m<sup>2</sup> depending on surface absorbency

## **PACKAGING:**

2,5 kg bag drum

10 kg bag drum

## **SHELF LIFE:**

It is 1 year from the date of production in its original packaging in dry and non-humid (temperature between +5 C and +25 C) environments. The lid of the containers should be tightly closed when not in use. It should be kept away from moisture.

## **STORAGE CONDITIONS:**

It should be stored in its unopened original package, in a moisture-free, dry and cool (temperature between +5 C and +25 C) environment. It should not be left under direct sunlight.

## **SECURITY:**

Avoid contact with skin and eyes. Use protective gloves, goggles and clothing. In case of eye contact, rinse with plenty of water and seek medical advice immediately. Keep out of reach of children. In case of skin contact, wash with plenty of water and soap. Do not swallow. For detailed information and recommendations, please refer to the Safety Data Sheet.

*DEKOSTAR San.ve Tic.Ltd. Şti. is not responsible for any application errors that may occur if the product is used for purposes other than its intended use or if the above-mentioned application conditions and recommendations are not followed. Dekostar reserves the right to change its products. Users should consider the latest edition of the Technical Data Sheet of the relevant product*